

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
11 August 2005 (11.08.2005)

PCT

(10) International Publication Number
WO 2005/072989 A1

(51) International Patent Classification⁷: **B60B 21/06**

(21) International Application Number:
PCT/AU2005/000123

(22) International Filing Date: 1 February 2005 (01.02.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2004900445 2 February 2004 (02.02.2004) AU

(71) Applicant (for all designated States except US): **VELOCITY BICYCLE ACCESSORIES PTY LTD** [AU/AU]; 24 Leonard Crescent, Brendale, Queensland 4500 (AU).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **SMITH, Grantly Ross** [AU/AU]; 280 Pringles Road, Samsonvale, Queensland 4520 (AU).


(74) Agent: **FISHER ADAMS KELLY**; Level 13, AMP Place, 10 Eagle Street, Brisbane, Queensland 4000 (AU).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO,

[Continued on next page]

(54) Title: WHEEL RIM



(57) Abstract: The present invention relates to a wheel rim (10, 200, 300, 310, 400, 500) comprising at least one track (30, 230, 330, 330a-330k, 430, 530) capable of operatively coupling to a spoke (40) and located on an inner surface (12) of the wheel rim (10, 200, 300, 310, 400, 500). The at least one track (30, 230, 330, 330a-330k, 430, 530) in one preferred form is capable of operatively coupling to at least one carriage (50, 50A, 50B, 250, 255, 350, 351, 450, 500), which is capable of operatively coupling to the end of a spoke (40). The carriage (50, 50A, 50B, 450, 550) in a preferred embodiment is adapted to retain a spoke nipple (41). The wheel rim (10, 200, 300, 310, 400, 500) is suitable for use with a bicycle wheel (60, 61, 62).



SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *with international search report*